
Product data sheet
Cable

Product description	**Raw cable, Contacts: 5 wires, unshielded, Standard, PUR, black, 5 x 0.34 mm², 100 m**
Area	**PUR cable**
Series	**769**
Part no.	**08 3082 000 000**

Illustration (may vary)



Technical data

General features

Part no.	08 3082 000 000
Connector design	Raw cable
Cable length	100 m
Version	Raw cable
Weight (g)	3495.00
Customs tariff number	85444995

Electrical parameters

EMC compliance	unshielded

Material

REACH SVHC	None (No pollutants)
SCIP number	SCIP-number not available

Cable data - Structure of the cable

Cable type	Standard
Cable diameter	5.0 mm
Cross section	5 x 0.34 mm²
Sheath material	PUR
Single-lead insulation	PP9Y halogen-free
Single-lead structure	43 x 0.10 mm
Cable color	black

Product data sheet
Cable

Product description	**Raw cable, Contacts: 5 wires, unshielded, Standard, PUR, black, 5 x 0.34 mm², 100 m**
Area	**PUR cable**
Series	**769**
Part no.	**08 3082 000 000**

Cable data - Electrical properties

Cable Insulation resistance	> 1000 MΩxKm
Operating voltage	≤ 300 V
Cable test voltage	≥ 2000 V effective
Conductor resistance	60 Ω/Km (20°C)

Cable data - Mechanical properties

Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø
Bending cycles	> 5 million
Permitted acceleration	5 m/s²
Travel distance, horizontal	at 5 m/s² -> 5 m
Travel distance, vertical	at 5 m/s² -> 2 m
Travel speed	at 5 m horizontal path -> 200 m/min

Cable data - Thermal properties

Temperature range cable in move from/to	-25 °C / 90 °C (UL +80 °C)
Temperature range cable fixed from/to	-50 °C / 90 °C (UL +80 °C)

Cable data - Other features

Halogen free	yes

Classifications

eCl@ss 11.1	27-44-01-90
ETIM 9.0	EC002638