Product data sheet


Automation technology - Voltage and Power Supply

Product description	**7/8" Lead-through for control cabinet, Contacts: 5, unshielded, pluggable, IP67, VDE, Rear mounting**
Area	**7/8"**
Series	**820**
Part no.	**09 2472 00 05**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	09 2472 00 05
Connector design	Lead-through for control cabinet
Version	Adapter
Connector locking system	screw
Termination	pluggable
Degree of protection	IP67
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	122.37
Customs tariff number	85369010

Electrical parameters

Rated voltage	300 V (600 V UL)
Rated impulse voltage	4000 V
Rated current	6.0 A
Pollution degree	3
Overvoltage category	III
Insulating material group	I
EMC compliance	unshielded

Product data sheet

Automation technology - Voltage and Power Supply

Product description	**7/8" Lead-through for control cabinet, Contacts: 5, unshielded, pluggable, IP67, VDE, Rear mounting**
Area	**7/8"**
Series	**820**
Part no.	**09 2472 00 05**

Material

Housing material	Zinc die-cast nickel-plated
Contact body material	PUR
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	f6c29127-c1a9-4f8e-96d7-3e1be735e103

Authorization/approvals

Approvals	VDE

Classifications

eCl@ss 11.1	27-44-01-09
ETIM 9.0	EC003569

Declarations of conformity


Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018

Product data sheet

Automation technology - Voltage and Power Supply

Product description	**7/8" Lead-through for control cabinet, Contacts: 5, unshielded, pluggable, IP67, VDE, Rear mounting**
Area	**7/8"**
Series	**820**
Part no.	**09 2472 00 05**

Assembly instructions / Panel cut-out



Product data sheet

Automation technology - Voltage and Power Supply

Product description	**7/8" Lead-through for control cabinet, Contacts: 5, unshielded, pluggable, IP67, VDE, Rear mounting**
Area	**7/8"**
Series	**820**
Part no.	**09 2472 00 05**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector to the device connector, we recommend tightening the threaded ring to 1.5 Nm. A suitable torque wrench is available as an accessory (order no. 07 0082 000).