Product data sheet


Automation technology - Sensors and actuators

Product description	**M12/M8 Adapter, Contacts: 3, unshielded, pluggable, IP67**
Area	**Adapter and Control cabinet feedthroughs**
Coding	**A-coded**
Series	**765**
Part no.	**09 5283 00 03**


Illustration (may vary)




Pin assignment plans



Scale drawing



Contact arrangement (Plug-in side)



Technical data

General features

Part no.	09 5283 00 03
Connector design	Adapter
Type standard	DIN EN 61076-2-104 DIN EN 61076-2-101
Coding	A-coded
Version	Adapter
Connector locking system	screw
Termination	pluggable
Degree of protection	IP67
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	12.00

Product data sheet

Automation technology - Sensors and actuators

Product description	**M12/M8 Adapter, Contacts: 3, unshielded, pluggable, IP67**
Area	**Adapter and Control cabinet feedthroughs**
Coding	**A-coded**
Series	**765**
Part no.	**09 5283 00 03**

Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	30 V
Rated impulse voltage	1500 V
Rated current	4.0 A
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	Macromelt
Contact body material	PA/PUR
Contact material	CuZn (brass) / CuSn (bronze)
Contact plating	Au (gold)
Locking material	Zinc die-cast nickel-plated
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	f792ae27-35c1-4d90-bc3c-774c1ce178bc

Classifications

eCl@ss 11.1	27-44-01-09
ETIM 9.0	EC003569

Declarations of conformity

RoHS Directive	EN IEC 63000:2018