
Product data sheet
Automation technology - Data transmission

Product description	**M12 Male panel mount connector, Contacts: 2, shielded, with cable assembled, IP68, PG 9, Profibus, PUR, violet, 1 x 2 x 0.25 mm², Front mounting, 0.5 m**
Area	**M12-B**
Coding	**B-coded**
Series	**766**
Part no.	**70 4433 247 04**

Illustration (may vary)




Scale drawing



Hexagon nut enclosed loose

Contact arrangement (Plug-in side)



1 nicht konfektioniert/*not assembled*
2 grün/*green*
3 nicht konfektioniert/*not assembled*
4 rot/*red*

You can find the assembly instructions on the next page.

Technical data

General features

Part no.	70 4433 247 04
Connector design	Male panel mount connector
Type standard	DIN EN 61076-2-101
Coding	B-coded
Cable length	0.5 m (Other lengths are available on request.)
Version	Connector pin straight
Connector locking system	screw
Termination	with cable assembled
Degree of protection	IP68
Connection cross-section	0.25 mm² / AWG 24
Temperature range from/to	-25 °C / 80 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	49.71
Customs tariff number	85444290
Country of Origin	HU

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	1500 V
Rated current	4.0 A
Insulation resistance	> 10^8 Ω
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	shielded

Product data sheet

Automation technology - Data transmission

Product description	**M12 Male panel mount connector, Contacts: 2, shielded, with cable assembled, IP68, PG 9, Profibus, PUR, violet, 1 x 2 x 0.25 mm², Front mounting, 0.5 m**
Area	**M12-B**
Coding	**B-coded**
Series	**766**
Part no.	**70 4433 247 04**

Shield connection	Shield on the housing

Material

Housing material	Zinc die-cast nickel-plated
Contact body material	PA
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	d37ba652-3c4f-4a21-9f2a-45a16d03cd73

Cable data - Structure of the cable

Cable type	Profibus
Cable diameter	7.8 mm
Cross section	1 x 2 x 0.25 mm²
Sheath material	PUR
Single-lead insulation	PE foam
Single-lead structure	19 x 0.127 mm
Cable color	violet

Cable data - Other features

Halogen free	yes

Classifications

eCl@ss 11.1	27-44-01-03


Product data sheet

Automation technology - Data transmission


Product description	**M12 Male panel mount connector, Contacts: 2, shielded, with cable assembled, IP68, PG 9, Profibus, PUR, violet, 1 x 2 x 0.25 mm², Front mounting, 0.5 m**
Area	**M12-B**
Coding	**B-coded**
Series	**766**
Part no.	**70 4433 247 04**

Assembly instructions / Panel cut-out

With flats as anti-rotation device



With bore hole



Installation direction: o-ring sits on chamfer.

Tightening moment

Metall housing/Plastic housing 1,25 Nm

Thickness of wall **Y** (mm)		
Version	**min** (mm)	**max** (mm)
Fastened from rear	2	3,5
Front fastened	2	4,5
positioning possible [1]	2	3,5
Screw clamp	2	3,5
Thread M12 x 1	2	3,0
Thread M14 x 1 [2]	[3]1,5/[4]2	6,5

Notes

[1] Do not attach a chamfer
[2] Wall thickness:
use nut 38 5385 100 001 up to 1,5 mm,
>1,5 mm cut thread
[3] Nut
[4] Thread in wall of housing

Product data sheet

Automation technology - Data transmission

Product description	**M12 Male panel mount connector, Contacts: 2, shielded, with cable assembled, IP68, PG 9, Profibus, PUR, violet, 1 x 2 x 0.25 mm², Front mounting, 0.5 m**
Area	**M12-B**
Coding	**B-coded**
Series	**766**
Part no.	**70 4433 247 04**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).