**Product data sheet**


# Automation technology - Voltage and Power Supply

| | |
|---|---|
| Product description | **M12 Male panel mount connector, Contacts: 4, unshielded, single wires, IP68, UL 2238, M20x1.5, Front mounting, potted** |
| Area | **M12-S** |
| Coding | **S-coded** |
| Series | **814** |
| Part no. | **76 0441 0136 00034-0200** |


### Illustration (may vary)



### Scale drawing




### Contact arrangement (Plug-in side)




**You can find the assembly instructions on the next page.**

## Technical data

### General features

| | |
|---|---|
| Part no. | 76 0441 0136 00034-0200<br>Alternative part no.: 09 0691 642 04 |
| Notice | Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right. |
| Connector design | Male panel mount connector |
| Type standard | DIN EN IEC 61076-2-111:2018-10;VDE 0687-76-2-111:2018-10 |
| Coding | S-coded |
| Wire length | 0.2 m (Standard 0.2 m. Other lengths are available on request). |
| Version | Connector pin straight |
| Connector locking system | screw |
| Termination | single wires |
| Degree of protection | IP68 |
| Connection cross-section | 1.50 mm² / AWG 16 |
| Temperature range from/to | -40 °C / 85 °C |
| Mechanical operation | > 100 Mating cycles |
| Weight (g) | 30.31 |
| Customs tariff number | 85369010 |
| Country of Origin | DE |

### Electrical parameters

| | |
|---|---|
| Rated voltage | 630 V |
| Rated impulse voltage | 6000 V |
| Rated current | 12.0 A |
| Pollution degree | 3 |
| Overvoltage category | III |

**Product data sheet**

# Automation technology - Voltage and Power Supply

| | |
|---|---|
| Product description | **M12 Male panel mount connector, Contacts: 4, unshielded, single wires, IP68, UL 2238, M20x1.5, Front mounting, potted** |
| Area | **M12-S** |
| Coding | **S-coded** |
| Series | **814** |
| Part no. | **76 0441 0136 00034-0200** |

| | |
|---|---|
| Insulating material group | II |
| EMC compliance | unshielded |

## Material

| | |
|---|---|
| Contact body material | PA |
| Contact material | CuZn (brass) |
| Contact plating | Au (gold) |
| REACH SVHC | CAS 7439-92-1 (Lead) |
| SCIP number | 57cb64a5-32fb-4114-94ad-bac8a3ab04b6 |

## Wire Data - Structure of the wire

| | |
|---|---|
| Cross section (mm²) | 4 x 1.50 mm² |
| Cross section (AWG) | 4 x AWG 16 |
| Wire diameter | 2,3 mm |
| Wire colors | yellow/green<br>black |
| Sheath material | mPPE |
| Wire material | Cu (tinned) |
| Wire structure | 40 x 0.210 mm |

## Wire Data - Electrical properties

| | |
|---|---|
| Rated voltage | 1000 V |
| Rated impulse voltage | 3000 V |
| Wire resistance | 14,6 Ω/Km (20°C) |
| Insulation resistance | 20.0 MΩ/Km (20 °C) |

## Wire Data - Thermal properties

| | |
|---|---|
| Temperature range wire in move from / to (°C) | -10 °C / 105 °C |
| Temperature range wire fixed from / to (°C) | -40 °C / 105 °C |

## Authorization/approvals

| | |
|---|---|
| Approvals | UL 2238 |

## Classifications

| | |
|---|---|
| eCl@ss 11.1 | 27-44-01-09 |
| ETIM 9.0 | EC003569 |

**Product data sheet**


# Automation technology - Voltage and Power Supply

| | |
|---|---|
| Product description | **M12 Male panel mount connector, Contacts: 4, unshielded, single wires, IP68, UL 2238, M20x1.5, Front mounting, potted** |
| Area | **M12-S** |
| Coding | **S-coded** |
| Series | **814** |
| Part no. | **76 0441 0136 00034-0200** |

## Assembly instructions / Panel cut-out

With flats as anti-rotation device

With bore hole





| Thread | Measures | | | Tightening torque | |
|---|---|---|---|---|---|
| **A** | **B** (mm) | **C** (mm) | **D** (mm) | Metal | Plastic |
| M16 x 1,5 | 17,0 | 16,1 | 13,5 | 1,25 Nm | 1,25 Nm |
| M20 x 1,5 | 21,6 | 20,1 | 17,8 | 2 Nm | 1,25 Nm |

| Thickness of wall Y (mm) | | |
|---|---|---|
| Version | **min** (mm) | **max** (mm) |
| Fastened from rear | 2 | 3,5 |
| Front fastened | 2 | 4,5 |
| Screw clamp | 2 | 3,5 |

Installation direction: o-ring sits on chamfer.

## Derating curve




Date: 03.10.2026

**Product data sheet**

# Automation technology - Voltage and Power Supply

| | |
|---|---|
| Product description | **M12 Male panel mount connector, Contacts: 4, unshielded, single wires, IP68, UL 2238, M20x1.5, Front mounting, potted** |
| Area | **M12-S** |
| Coding | **S-coded** |
| Series | **814** |
| Part no. | **76 0441 0136 00034-0200** |

## Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).

In the case of cable connectors with a metal threaded ring, it is imperative to ensure a connection with the PE protective contact of the appliance connector. Connecting cables between appliance connectors that are not connected to the PE contact are not permitted. The user must ensure a continuous connection of the protective earth conductor.