Product data sheet


Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 4, unshielded, single wires, IP67, UL 2238, M10x0.75, Front mounting, potted**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**76 6219 1111 00004-0200**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	76 6219 1111 00004-0200 Alternative part no.: 09 3421 00 04
Notice	Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right.
Connector design	Male panel mount connector
Type standard	DIN EN 61076-2-104
Coding	A-coded
Wire length	0.2 m (Standard 0.2 m. Other lengths are available on request).
Version	Connector pin straight
Connector locking system	snap-in, screw
Termination	single wires
Degree of protection	IP67
Connection cross-section	0.25 mm² / AWG 24
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	16.75
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	50 V (AC) / 60 V (DC)
Rated impulse voltage	1500 V

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 4, unshielded, single wires, IP67, UL 2238, M10x0.75, Front mounting, potted**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**76 6219 1111 00004-0200**

Rated current	4.0 A
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	Zinc die-cast nickel-plated
Contact body material	PA black
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	a8b72d8d-7862-4c1e-a847-238b35936f46

Wire Data - Structure of the wire

Cross section (mm²)	4 x 0.25 mm²
Cross section (AWG)	4 x AWG 24
Wire diameter	1,5 mm
Wire colors	white brown blue black
Sheath material	PVC
Wire material	Cu (tinned)
Wire structure	7 x 0.203 mm

Wire Data - Electrical properties

Rated voltage	300 V
Rated impulse voltage	3000 V
Wire resistance	90 Ω/Km (20°C)
Insulation resistance	20.0 MΩ/Km (20 °C)

Wire Data - Thermal properties

Temperature range wire in move from / to (°C)	-10 °C / 105 °C
Temperature range wire fixed from / to (°C)	-30 °C / 105 °C

Authorization/approvals

Approvals	UL 2238

Classifications


eCl@ss 11.1	27-44-01-03
ETIM 9.0	EC003570

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 4, unshielded, single wires, IP67, UL 2238, M10x0.75, Front mounting, potted**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**76 6219 1111 00004-0200**

Assembly instructions / Panel cut-out



thread E	A	B	C	D
M8 x 0,5	8,1	2,5	3,5	7,1
M8 x 1	8,1	2,5	3,5	7,1
M10 x 0,75	10,1	2,5	5,0	9,1

Tightening torque 1 Nm

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 4, unshielded, single wires, IP67, UL 2238, M10x0.75, Front mounting, potted**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**76 6219 1111 00004-0200**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).