Product data sheet


Automation technology - Voltage and Power Supply

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 2+PE, unshielded, moulded on the cable, IP68, UL 2238, PUR, black, 3 x 1.50 mm², 5 m**
Area	**M12-S**
Coding	**S-coded**
Series	**814**
Part no.	**77 0690 0689 50703-0500**


Illustration (may vary)



Scale drawing




Contact arrangement (Plug-in side)



1 *black*
3 *black*
PE *yellow/green*

Contact arrangement (Plug-in side)



1 *black*
3 *black*
PE *yellow/green*

Cable length tolerance

cable length	*tolerance*
≥ 0,10 m	+ 0,03 m
≥ 0,20 m	+ 0,04 m
≥ 0,50 m	+ 0,07 m
≥ 1,00 m	+ 0,10 m
≥ 2,00 m	+ 0,15 m
≥ 5,00 m	+ 0,20 m
≥ 10,0 m	+ 0,25 m
≥ 20,0 m	+ 0,35 m

Technical data

General features

Part no.	77 0690 0689 50703-0500
Connector design	Connecting cable male cable connector - female cable connector
Type standard	DIN EN IEC 61076-2-111:2018-10;VDE 0687-76-2-111:2018-10
Coding	S-coded
Cable length	5 m (Other lengths are available on request.)
Version	Double ended cordsets

Product data sheet

Automation technology - Voltage and Power Supply

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 2+PE, unshielded, moulded on the cable, IP68, UL 2238, PUR, black, 3 x 1.50 mm², 5 m**
Area	**M12-S**
Coding	**S-coded**
Series	**814**
Part no.	**77 0690 0689 50703-0500**

Connector locking system	screw
Termination	moulded on the cable
Degree of protection	IP68
Connection cross-section	1.50 mm² / AWG 16
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	651.2
Customs tariff number	85444290
Country of Origin	DE

Electrical parameters

Rated voltage	630 V
Rated impulse voltage	6000 V
Rated current	12.0 A
Pollution degree	3
Overvoltage category	III
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	PA (UL94 V-0)
Contact body material	PA (UL94 V-0)
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	3795b5f5-1b90-45b5-8375-f71e2612fe31

Cable data - Structure of the cable

Cable diameter	7.5 mm
Cross section	3 x 1.50 mm²
Sheath material	PUR
Single-lead insulation	PP
Single-lead structure	84 x 0.15 mm
Cable color	black

Cable data - Thermal properties

Temperature range cable in move from/to	-30 °C / 90 °C
Temperature range cable fixed from/to	-50 °C / 90 °C

Cable data - Other features

Halogen free	yes

Product data sheet

Automation technology - Voltage and Power Supply

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 2+PE, unshielded, moulded on the cable, IP68, UL 2238, PUR, black, 3 x 1.50 mm², 5 m**
Area	**M12-S**
Coding	**S-coded**
Series	**814**
Part no.	**77 0690 0689 50703-0500**

Authorization/approvals

Approvals	UL 2238


Classifications

eCl@ss 11.1	27-06-03-11
ETIM 9.0	EC002638

Declarations of conformity

Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018
RoHS Directive	EN IEC 63000:2018

Derating curve



Product data sheet

Automation technology - Voltage and Power Supply

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 2+PE, unshielded, moulded on the cable, IP68, UL 2238, PUR, black, 3 x 1.50 mm², 5 m**
Area	**M12-S**
Coding	**S-coded**
Series	**814**
Part no.	**77 0690 0689 50703-0500**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).

In the case of cable connectors with a metal threaded ring, it is imperative to ensure a connection with the PE protective contact of the appliance connector. Connecting cables between appliance connectors that are not connected to the PE contact are not permitted. The user must ensure a continuous connection of the protective earth conductor.