Product data sheet


Automation technology - Sensors and actuators

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 4, unshielded, moulded on the cable, IP67/IP69K, Ecolab, FDA compliant, Special TPE, grey, 4 x 0.34 mm², Food & Beverage, stainless steel, 2 m**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 3730 3729 40404-0200**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



Cable length tolerance

cable length	tolerance
≥ 0,10 m	+ 0,03 m
≥ 0,20 m	+ 0,04 m
≥ 0,50 m	+ 0,07 m
≥ 1,00 m	+ 0,10 m
≥ 2,00 m	+ 0,15 m
≥ 5,00 m	+ 0,20 m
≥ 10,0 m	+ 0,25 m
≥ 20,0 m	+ 0,35 m

Technical data

General features

Part no.	77 3730 3729 40404-0200
Connector design	Connecting cable male cable connector - female cable connector
Type standard	DIN EN 61076-2-101
Coding	A-coded
Cable length	2 m (Standard 1 m and 2 m. Other lengths are available on request.)
Version	Double ended cordsets
Connector locking system	screw

Product data sheet

Automation technology - Sensors and actuators

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 4, unshielded, moulded on the cable, IP67/IP69K, Ecolab, FDA compliant, Special TPE, grey, 4 x 0.34 mm², Food & Beverage, stainless steel, 2 m**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 3730 3729 40404-0200**

Termination	moulded on the cable
Degree of protection	IP67/IP69K
Connection cross-section	0.34 mm² / AWG 22
Temperature range from/to	-40 °C / 105 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	126.6
Customs tariff number	85444290
Country of Origin	DE

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	2500 V
Rated current	4.0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	PP
Contact body material	PP
Contact material	CuZn (brass) / CuSn (bronze)
Contact plating	Au (gold)
Locking material	Stainless steel
REACH SVHC	None (No pollutants)
SCIP number	SCIP-number not available

Cable data - Structure of the cable

Cable diameter	4.7 mm
Cross section	4 x 0.34 mm²
Sheath material	Special TPE
Single-lead insulation	modified TPE
Single-lead structure	43 x 0.10 mm
Cable color	grey

Cable data - Mechanical properties

Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø

Cable data - Thermal properties

Temperature range cable in move from/to	-25 °C / 105 °C
Temperature range cable fixed from/to	-50 °C / 105 °C

Product data sheet

Automation technology - Sensors and actuators

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 4, unshielded, moulded on the cable, IP67/IP69K, Ecolab, FDA compliant, Special TPE, grey, 4 x 0.34 mm², Food & Beverage, stainless steel, 2 m**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 3730 3729 40404-0200**

Cable data - Other features

Halogen free	yes

Authorization/approvals

Approvals	Ecolab, FDA compliant

Classifications

eCl@ss 11.1	27-06-03-11
ETIM 9.0	EC002638

Declarations of conformity

Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018
RoHS Directive	EN IEC 63000:2018

Product data sheet

Automation technology - Sensors and actuators

Product description	**M12 Connecting cable male cable connector - female cable connector, Contacts: 4, unshielded, moulded on the cable, IP67/IP69K, Ecolab, FDA compliant, Special TPE, grey, 4 x 0.34 mm², Food & Beverage, stainless steel, 2 m**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 3730 3729 40404-0200**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).

The protection class specification applies on condition that the four mounting holes are made as blind holes.