Product data sheet


Automation technology - Sensors and actuators

Product description	**M12 Female terminating connector, Contacts: 5, unshielded, IP69K, CAN-Bus**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 9840 0000 00005**


Illustration (may vary)




Pin assignment plans



Scale drawing



Contact arrangement (Plug-in side)



Technical data

General features

Part no.	77 9840 0000 00005
Connector design	Female terminating connector
Type standard	DIN EN 61076-2-101
Coding	A-coded
Version	Female terminating connector

Product data sheet

Automation technology - Sensors and actuators

Product description	**M12 Female terminating connector, Contacts: 5, unshielded, IP69K, CAN-Bus**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 9840 0000 00005**

Connector locking system	screw
Degree of protection	IP69K
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	12.35
Customs tariff number	85444290
Country of Origin	DE

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	1500 V
Rated current	4.0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	PUR
Contact body material	PUR
Contact material	CuSn (bronze)
Contact plating	Au (gold)
Locking material	Zinc die-cast nickel-plated
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	b8b0f472-7ec1-45e3-94af-8b5981bb590d

Cable data - Structure of the cable

Cable type	CAN-Bus

Classifications

eCl@ss 11.1	27-06-03-11
ETIM 9.0	EC002638

Declarations of conformity

Low Voltage Directive	EN 60204-1:2018
RoHS Directive	EN IEC 63000:2018
Ecodesign Directive	2009/125/EG

Product data sheet

Automation technology - Sensors and actuators

Product description	**M12 Female terminating connector, Contacts: 5, unshielded, IP69K, CAN-Bus**
Area	**M12-A**
Coding	**A-coded**
Series	**763**
Part no.	**77 9840 0000 00005**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).

The protection class specification applies on condition that the four mounting holes are made as blind holes.