
Product data sheet
Miniature connectors

Product description	**Snap-In Female cable connector, Contacts: 3, unshielded, moulded on the cable, VDE, PUR, 2 m**
Area	**Snap-In IP67**
Series	**720**
Part no.	**79 9150 120 03**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



Cable length tolerance

cable length	tolerance
≥ 0,10 m	+ 0,03 m
≥ 0,20 m	+ 0,04 m
≥ 0,50 m	+ 0,07 m
≥ 1,00 m	+ 0,10 m
≥ 2,00 m	+ 0,15 m
≥ 5,00 m	+ 0,20 m
≥ 10,0 m	+ 0,25 m
≥ 20,0 m	+ 0,35 m

Technical data

General features

Part no.	79 9150 120 03
Connector design	Female cable connector
Cable length	2 m (Standard 2 m and 5 m. Other lengths are available on request.)
Termination	moulded on the cable
Weight (g)	145.00
Customs tariff number	85444290
Country of Origin	DE

Product data sheet

Miniature connectors

Product description	**Snap-In Female cable connector, Contacts: 3, unshielded, moulded on the cable, VDE, PUR, 2 m**
Area	**Snap-In IP67**
Series	**720**
Part no.	**79 9150 120 03**

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	2500 V
Rated current	7.0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	2
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded
Voltage	2950 V DC

Material

Housing material	PUR
Contact body material	PA (UL94 V-0)
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	0d97c54f-efc8-4f36-8f67-2f23601ba625

Cable data - Structure of the cable

Cable diameter	6.8 mm
Sheath material	PUR
Single-lead insulation	EPK

Cable data - Electrical properties

Conductor resistance	26.7 Ω/Km (20°C)

Cable data - Mechanical properties

Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø

Cable data - Thermal properties

Temperature range cable in move from/to	-5 °C / 70 °C
Temperature range cable fixed from/to	-40 °C / 80 °C

Cable data - Other features

Halogen free	yes

Authorization/approvals

Approvals	VDE

Product data sheet

Miniature connectors

Product description	**Snap-In Female cable connector, Contacts: 3, unshielded, moulded on the cable, VDE, PUR, 2 m**
Area	**Snap-In IP67**
Series	**720**
Part no.	**79 9150 120 03**

Classifications

eCl@ss 11.1	27-06-03-11
ETIM 9.0	EC002638

Product data sheet
Miniature connectors

Product description	**Snap-In Female cable connector, Contacts: 3, unshielded, moulded on the cable, VDE, PUR, 2 m**
Area	**Snap-In IP67**
Series	**720**
Part no.	**79 9150 120 03**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".