Product data sheet


Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 12, unshielded, THT, IP67/IP69K, UL 2238, M8x1.0, Rear mounting, screwable from the front, potted**
Area	**M8**
Coding	**C-coded**
Series	**718**
Part no.	**86 6119 1100 00012**


Illustration (may vary)




Conductor layout



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 12, unshielded, THT, IP67/IP69K, UL 2238, M8x1.0, Rear mounting, screwable from the front, potted**
Area	**M8**
Coding	**C-coded**
Series	**718**
Part no.	**86 6119 1100 00012**

General features

Part no.	86 6119 1100 00012
Connector design	Male panel mount connector
Type standard	DIN EN 61076-2-104
Coding	C-coded
Connector locking system	screw
Termination	THT
Degree of protection	IP67/IP69K
Mechanical operation	> 100 Mating cycles
Weight (g)	3.92
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	32 V
Rated impulse voltage	500 V
Rated current	1.0 A
Insulation resistance	> 10^8 Ω
Pollution degree	3
Overvoltage category	II
Insulating material group	I
EMC compliance	unshielded
Voltage	500 V DC

Material

Housing material	CuZn (Brass nickel plated)
Contact body material	PUR black
Contact material	CuZn (brass) / CuSn (bronze)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	af90f72c-2843-4871-9ddf-a9ad1c1b5155

Authorization/approvals

Approvals	UL 2238

Classifications


ETIM 9.0	EC003569

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 12, unshielded, THT, IP67/IP69K, UL 2238, M8x1.0, Rear mounting, screwable from the front, potted**
Area	**M8**
Coding	**C-coded**
Series	**718**
Part no.	**86 6119 1100 00012**

Assembly instructions / Panel cut-out



Gewinde E	A	B	C
M8 x 1	8,1	2,0	3,5
M10 x 0,75	10,1	2,0	6,5
M12 x 1	12,1	2,5	4,5

Anzugsdrehmoment 1 Nm

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male panel mount connector, Contacts: 12, unshielded, THT, IP67/IP69K, UL 2238, M8x1.0, Rear mounting, screwable from the front, potted**
Area	**M8**
Coding	**C-coded**
Series	**718**
Part no.	**86 6119 1100 00012**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).