Product data sheet


Automation technology - Sensors and actuators

Product description	**M8 Male receptacle, Contacts: 3, unshielded, THT, IP67, Front mounting**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**86 6819 0000 00703**


Illustration (may vary)




Conductor layout



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	86 6819 0000 00703
Connector design	Male receptacle
Type standard	DIN EN 61076-2-104
Coding	A-coded

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male receptacle, Contacts: 3, unshielded, THT, IP67, Front mounting**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**86 6819 0000 00703**

Version	Connector pin straight
Connector locking system	screw
Termination	THT
Degree of protection	IP67
Connection cross-section	0.25 mm² / AWG 24
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	1.14
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	50 V (AC) / 60 V (DC)
Rated impulse voltage	800 V
Rated current	4.0 A
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	CuZn (Brass nickel plated)
Contact body material	PA
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	af93f9d1-d282-43dd-84d6-96c2aba17ea3

Classifications


eCl@ss 11.1	27-44-01-09
ETIM 9.0	EC003569

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male receptacle, Contacts: 3, unshielded, THT, IP67, Front mounting**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**86 6819 0000 00703**

Assembly instructions / Panel cut-out



Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Male receptacle, Contacts: 3, unshielded, THT, IP67, Front mounting**
Area	**M8**
Coding	**A-coded**
Series	**718**
Part no.	**86 6819 0000 00703**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).