Product data sheet


Automation technology - Voltage and Power Supply

Product description	**M12 Male cable connector, Contacts: 4, 6.0-8.0 mm, unshielded, screw clamp, IP67, stainless steel**
Area	**M12-T**
Coding	**T-coded**
Series	**813**
Part no.	**99 0629 60 04**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 0629 60 04
Connector design	Male cable connector
Coding	T-coded
Version	Connector pin straight
Connector locking system	screw
Termination	screw clamp
Degree of protection	IP67
Connection cross-section	max. 1.50 mm² / AWG 16
Cable outlet	6.0-8.0 mm
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	22.65
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	63 V
Rated impulse voltage	1500 V
Rated current	12.0 A
Pollution degree	3

Product data sheet

Automation technology - Voltage and Power Supply

Product description	**M12 Male cable connector, Contacts: 4, 6.0-8.0 mm, unshielded, screw clamp, IP67, stainless steel**
Area	**M12-T**
Coding	**T-coded**
Series	**813**
Part no.	**99 0629 60 04**

Overvoltage category	III
Insulating material group	III
EMC compliance	unshielded

Material


Housing material	PA
Contact body material	PA
Contact material	CuZn (brass)
Contact plating	Au (gold)
Locking material	Stainless steel
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	69b97b87-7291-482e-bb83-5c822e7d8ed9

Trade-Compliance

Copper (9903.78.01)	0.000221 kg

Assembly instructions

1. Bead pre-assembled housing to cable (consisting of: sleeve, seal, pinch ring and pressing screw).
2. Dismantle cable and strip single wires.
3. Screw on single wires (0.4 Nm).
4. Screw sleeve to male/female insert.
5. Push seal and pinch ring into coupling sleeve.
6. Tighten pressing screw.



Product data sheet

Automation technology - Voltage and Power Supply

Product description	**M12 Male cable connector, Contacts: 4, 6.0-8.0 mm, unshielded, screw clamp, IP67, stainless steel**
Area	**M12-T**
Coding	**T-coded**
Series	**813**
Part no.	**99 0629 60 04**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).