
Product data sheet
Power connectors

Product description	**RD30 Male angled connector, Contacts: 4+PE, 12.0-14.0 mm, unshielded, screw clamp, IP65, ESTI+, VDE**
Area	**RD30**
Series	**694**
Part no.	**99 0709 72 05**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 0709 72 05
Connector design	Male angled connector
Version	Connector pin angled
Connector locking system	screw
Termination	screw clamp
Degree of protection	IP65
Connection cross-section	2.50 mm² / AWG 14
Cable outlet	12.0-14.0 mm
Twistability	45° (8 coding options)
Temperature range from/to	-40 °C / 100 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	87.84
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	400 V
Rated impulse voltage	6000 V
Rated current	20.0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	3
Overvoltage category	III
Insulating material group	III

Product data sheet

Power connectors

Product description	**RD30 Male angled connector, Contacts: 4+PE, 12.0-14.0 mm, unshielded, screw clamp, IP65, ESTI+, VDE**
Area	**RD30**
Series	**694**
Part no.	**99 0709 72 05**

EMC compliance	unshielded

Material

Housing material	PA
Contact body material	PA (UL94 HB)
Contact material	CuZn (brass)
Contact plating	Ag (silver)
REACH SVHC	CAS 96-45-7|CAS 7439-92-1 (Imidazolidine-2-thione|Lead)
SCIP number	d35bcd96-664d-4a3e-a1fd-ba1c2f834b7a

Authorization/approvals

Approvals	ESTI+, VDE

Classifications

eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018

Trade-Compliance


Copper (9903.78.01)	0.000221 kg

Product data sheet
Power connectors

Product description	**RD30 Male angled connector, Contacts: 4+PE, 12.0-14.0 mm, unshielded, screw clamp, IP65, ESTI+, VDE**
Area	**RD30**
Series	**694**
Part no.	**99 0709 72 05**

Assembly instructions

1. *Unscrew the clamping screws until the holes for single wires are completely free.*
2. *Bead parts of the cable clamp and coupling sleeve onto the cable.*
3. *Dismantle cable.*
4. *Strip, twist and screw on single wires.*
5. *Only female insert: mount o-ring.*
6. *Snap on the threaded ring.*
7. *Screw on the sleeve.*
8. *Tighten pressing screw.*




Date: 03.10.2026

Product data sheet
Power connectors

Product description	**RD30 Male angled connector, Contacts: 4+PE, 12.0-14.0 mm, unshielded, screw clamp, IP65, ESTI+, VDE**
Area	**RD30**
Series	**694**
Part no.	**99 0709 72 05**

Derating curve



Date: 03.10.2026

Product data sheet
Power connectors

Product description	**RD30 Male angled connector, Contacts: 4+PE, 12.0-14.0 mm, unshielded, screw clamp, IP65, ESTI+, VDE**
Area	**RD30**
Series	**694**
Part no.	**99 0709 72 05**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector to the device connector, we recommend tightening the threaded ring to 1 Nm. A suitable torque wrench is available as an accessory (order no. 07 0082 000).