
Product data sheet
Medical Grade Connectors

Product description	**Bayonet Male cable connector, Contacts: 8, 4.0-6.0 mm, unshielded, solder, IP67 (when unplugged as well)**
Area	**Bayonet NCC**
Series	**770**
Part no.	**99 0771 471 08**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 0771 471 08
Connector design	Male cable connector
Version	Connector pin straight
Connector locking system	Bayonet
Termination	solder
Degree of protection	IP67 (when unplugged as well)
Connection cross-section	0.25 mm² / AWG 24
Cable outlet	4.0-6.0 mm
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 5000 Mating cycles
Weight (g)	10.02
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	175 V
Rated impulse voltage	1750 V
Rated current	2.0 A
Pollution degree	2
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Product data sheet
Medical Grade Connectors

Product description	**Bayonet Male cable connector, Contacts: 8, 4.0-6.0 mm, unshielded, solder, IP67 (when unplugged as well)**
Area	**Bayonet NCC**
Series	**770**
Part no.	**99 0771 471 08**

Material

Housing material	PA
Contact body material	PA (UL94 HB)
Contact material	CuZn (brass)
Contact plating	Au (gold)
Locking material	PA green
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	de9ac2ab-a202-409a-98e9-d66047f9000a

Classifications


eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018

Assembly instructions

1. *Strip to 9 mm length and take off the cable jacket.*
2. *Bead pressing screw, pinch ring, seal and distance sleeve to cable.*
3. *Strip the insulation off the wires (L = 3 mm) and tin them.*
4. *Solder inserts.*
5. *Put bayonet adapter to the thread of the distance sleeve and screw it with slight pressure in the direction of the arrow.*
6. *Push pinch ring over sealing ring to block.*
7. *Push pressing screw together with clamp-sealing unit towards distance sleeve and screw tightly.*



Date: 03.10.2026

Product data sheet
Medical Grade Connectors

Product description	**Bayonet Male cable connector, Contacts: 8, 4.0-6.0 mm, unshielded, solder, IP67 (when unplugged as well)**
Area	**Bayonet NCC**
Series	**770**
Part no.	**99 0771 471 08**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".