
Product data sheet
Subminiature connectors

Product description	**Bayonet Female cable connector, Contacts: 3, 4.0-5.0 mm, unshielded, solder, IP40**
Area	**Bayonet**
Series	**710**
Part no.	**99 0976 102 03**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 0976 102 03
Connector design	Female cable connector
Version	Connector socket straight
Connector locking system	Bayonet
Termination	solder
Degree of protection	IP40
Connection cross-section	max. 0.25 mm² / AWG 24
Cable outlet	4.0-5.0 mm
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	2.48
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	125 V
Rated impulse voltage	1500 V
Rated current	4.0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	1
Overvoltage category	II
Insulating material group	III
EMC compliance	unshielded

Product data sheet
Subminiature connectors

Product description	**Bayonet Female cable connector, Contacts: 3, 4.0-5.0 mm, unshielded, solder, IP40**
Area	**Bayonet**
Series	**710**
Part no.	**99 0976 102 03**

Material

Housing material	PA
Contact body material	PA (UL94 V-0)
Contact material	CuSn (bronze)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	a2fd8715-50a9-4da3-8039-1288523a0c77

Classifications


eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018

Assembly instructions

1. *Bead pressing screw to cable.*
2. *Dismantle cable to 15 mm length.*
3. *Strip and solder single wires.*
4. *Place female insert into carrier sleeve part 2 (lower part grey).*
4. *Mount carrier sleeve part 1 (upper part black) on carrier sleeve part 2 (lower part grey).*
5. *Snap assembly group into coupling ring.*
6. *Tighten pressing screw.*



Product data sheet
Subminiature connectors

Product description	**Bayonet Female cable connector, Contacts: 3, 4.0-5.0 mm, unshielded, solder, IP40**
Area	**Bayonet**
Series	**710**
Part no.	**99 0976 102 03**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".