
Product data sheet
Miniature connectors

Product description	**M16 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, shieldable, solder, IP68, UL 2238, Short version**
Area	**M16 IP67**
Series	**423**
Part no.	**99 5122 60 06**


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 5122 60 06
Connector design	Female cable connector
Type standard	DIN EN 61076-2-106
Version	Connector socket straight
Connector locking system	screw
Termination	solder
Degree of protection	IP68
Connection cross-section	max. 0.75 mm² / AWG 18
Cable outlet	4.1-7.8 mm
Temperature range from/to	-30 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	43.23
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	150 V
Rated impulse voltage	1500 V
Rated current	5.0 A
Pollution degree	2
Overvoltage category	II
Insulating material group	III
EMC compliance	shieldable

Product data sheet

Miniature connectors

Product description	**M16 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, shieldable, solder, IP68, UL 2238, Short version**
Area	**M16 IP67**
Series	**423**
Part no.	**99 5122 60 06**

Shield connection	cable clamp

Material

Housing material	CuZn (Brass nickel plated)
Contact body material	PBT
Contact material	CuSn (bronze)
Contact plating	Ag (silver)
Locking material	CuZn (brass)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	f12c1773-1102-486a-9642-7a3c040adcae

Authorization/approvals

Approvals	UL 2238

Classifications

ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	EN 60529:1991 | EN 60204-1:2018
RoHS Directive	EN IEC 63000:2018

Trade-Compliance


Copper (9903.78.01)	0.000321 kg

Product data sheet
Miniature connectors

Product description	**M16 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, shieldable, solder, IP68, UL 2238, Short version**
Area	**M16 IP67**
Series	**423**
Part no.	**99 5122 60 06**

Assembly instructions

1. Bead pressing screw, thrust collar, seal, sleeve and cable clamp to cable.
2. Dismantle cable to 17 mm length.
3. Strip single wires.
4. Solder single wires and insert contact insert into coupling ring.
5. Mount clamping device.
6. Screw sleeve into coupling ring.
7. Tighten pressing screw.



Product data sheet
Miniature connectors

Product description	**M16 Female cable connector, Contacts: 6 (06-a), 4.1-7.8 mm, shieldable, solder, IP68, UL 2238, Short version**
Area	**M16 IP67**
Series	**423**
Part no.	**99 5122 60 06**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).