

NAC3M-TRUE1-CG

The powerCON TRUE1 is a locking true mains connector for harsh and demanding applications. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 is a connector series with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live. The new cable entry achieves IP65, IP66 and IP67.



Features & Benefits

- ✓ Heavy duty sealed power connector for harsh and demanding environment
- ✓ Uses high impact UV-resistant materials
- ✓ Lockable single phase connector
- ✓ Extremely robust and reliable
- ✓ ENEC and VDE certified according to IEC 60320-1 and EN IEC 60320-1
- ✓ UL and CSA Certified According to UL 60320-1 and CSA 22.2 No. 60320-1

- ✓ IP65, IP66 and IP67 (mated)
- ✓ True mains connector with breaking capacity (CBC)
- ✓ Easy and reliable twist lock system
- ✓ Unique NEUTRIK locking bushing and strain relief for cable diameters 8 mm to 13 mm (0.31– 0.51 inches)

Product related questions and answers

Question	Answer
When is the IEC 60799 relevant?	This standard applies for "Cord Sets And Interconnection Cord Sets" and therefore covers cables to the mains and cables acting as power interconnections.
Why is the bushing loose in one direction?	This is to meet the standards requirement to prevent disassembling by hand. In order to open the cable entry a special tool will be required.

Technical Information

Produkte	
Title	NAC3M-TRUE1-CG
Product family	powerCON® TRUE1

Elektrisch

Contact resistance	$\leq 2 \text{ m}\Omega$
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	$> 1 \text{ G}\Omega$ (after damp and heat test IEC 68-2-30)
Number of electrical contacts	2 + PE
Rating Europe	16 A / 250 V AC according to EN IEC 60320-1
Rating America	20 A / 250 V AC according to UL 60320-1 20 A / 250 V AC according to CSA C22.2 No. 60320-1

Mechanische Daten

Cable O.D.	8 - 13 mm (0.31 – 0.51 inches)
Lifetime	> 5000 mating cycles
Wiresize (mm ²)	1.5 - 2.5 mm ²
Wiresize (AWG)	12 AWG

Material

Contact plating	2 μm Ag
Locking element	Polyamide (PA 66)
Contacts	Copper Alloy
Insert	Polyamide (PA 66)
Shell	Polyamide (PA 66)
Strain relief	Polyketon

Umwelt	
Flammability	UL 94 V-0
Protection class	IP65, IP66 and IP67 (mated)
UV resistance	F1 rated material withstands UV exposure
Operating temperature range	-30°C to +80°C according to IEC 61984 -5°C to +40°C according to IEC 60320-1