

Pushbutton, 15.2 mm, quick connector, momentary contact function, 1 NO, bezel red



Description

Pushbutton with mounting hole diameter 15.2 mm

Pushbutton with mounting hole diameter 15.2 mm, solder/quick-connect terminal for 6.3 x 0.8 mm or 2 x 2.8 x 0.8 mm



technical data

> general

| | |
|---|-------------------------------|
| Bezel color | red |
| Property of bezel / mushroom | opaque |
| Collar shape | round |
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 85 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 90 °C |
| illuminated | No |
| Packaging | Box |
| Packaging unit | 100 pcs. |
| Net weight | 5 g |
| Operating life | 25,000 cycles |
| B10 | 32,500 cycles |
| Degree of protection, front side, according to DIN EN 60529 | IP40 IP65 with sealing cap |
| Minimum order quantity (MOQ) | 100 pcs. |
| RoHS compliant | Yes |
| REACH compliant | Yes |
| Country of origin | HU |

direct links

> [RAFI eCatalog](#)

> mounting diameters

| | |
|---------------------------|---------|
| Outside dimension, length | 19 mm |
| Outside dimension, width | 19 mm |
| Outside dimension, height | 29.7 mm |
| Mounting hole | 15.2 mm |
| Mounting depth | 21.5 mm |
| Installation height | 8.2 mm |

> mechanical data

| | |
|-----------------------|---|
| Terminal on the rear | Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 |
| Fixing | Threaded ring |
| Actuation function | momentary contact function |
| Operating force, max. | 7.5 N |

| | |
|------------------------|----------------|
| Operating travel, max. | 3 mm |
| Contact function | 1 NO |
| Contact system | Bridge contact |
| Contact material | Silver |
| Solderability | No |

> electrical data

| | |
|---------------------|-------|
| Rated voltage, max. | 250 V |
| Rated current, max. | 0.7 A |