

## RAFIX 22 QR, buzzer, round collar, 70 dB



### Description

Acoustic signal transmitter matching the design of the RAFIX 22 QR actuating elements with round collar shape.



### technical data

#### > general

Bezel color	slate gray
Property of bezel / mushroom	opaque
Collar shape	round
Frequency	2,400 - 3100 Hz
Operating temperature, min.	-25 °C
Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
Volume 1 m	70 dB
illuminated	No
Tone type	Continuous tone
Packaging	Box
Packaging unit	2 pcs.
Net weight	29.3 g
Degree of protection, front side, according to DIN EN 60529	IP65
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
Minimum order quantity (MOQ)	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes
Country of origin	HU

#### > mounting diameters

Outside dimension, length	65.75 mm
Outside dimension, width	48.8 mm
Outside dimension, height	30 mm
Mounting hole	22.3 mm
Mounting depth	56.4 mm
Installation height	9.8 mm
Grid, min.	50 x 30 mm
Collar dimension	ø 29,8 mm

#### direct links

> [RAFI eCatalog](#)

**> mechanical data**

Fixing	Threaded ring
Threaded ring torque, max.	1.2 Nm

**> electrical data**

Voltage type	DC
Rated operating voltage	12 V
Operating current, max.	25 mA
Power loss	0.30000 W
Maximum connection cross section	1.5 mm <sup>2</sup>
Minimum connection cross section	0.25 mm <sup>2</sup>

**Use according to UL:**

---

RAFIX control devices are defined at RAFI as modular elements, consisting of an actuating element, if necessary a coupling and an individual contact or lighting unit.

Actuating elements (such as pushbuttons, emergency stop actuators, etc.) have the intended tactility, reset and function only when assembled with the appropriate switching elements.

**drawings**

---

**front panel drawing**

