

Signal lamp with lamp socket, BA 9s, 16.2 mm, IP40, housing, 250 Volt, Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated



Description

Signal lamps for LEDs or filament/neon lamps with BA 9 s socket, mounting hole diameter 16.2 mm



technical data

> general

illuminated	Yes
Lamp socket	BA9s
Packaging unit	10 pcs.
Net weight	6.9 g
Degree of protection, front side, according to DIN EN 60529	IP40
Minimum order quantity (MOQ)	100 pcs.
RoHS compliant	Yes
REACH compliant	Yes
Country of origin	HU

direct links

> [RAFI eCatalog](#)

> mounting diameters

Outside dimension, length	20 mm
Outside dimension, width	20 mm
Outside dimension, height	60.8 mm
Mounting hole	16.2 mm
Mounting depth	45.8 mm
Installation height	15 mm
Collar dimension	20 mm

> mechanical data

Terminal on the rear	Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated
Fixing	Threaded ring
Solderability	Yes

> electrical data

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which may change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.

date: May 4, 2026 page: 1/3

RAFI GmbH & Co. KG

Ravensburger Str. 128-134
88276 Berg / Ravensburg
Germany
www.rafi-group.com,
info.headquarters@rafi-group.com

Operating voltage of the luminous element, max. 250 V

drawings

Mounting hole drawing