



**716M-NF**

Coaxial Adapter 716M-NF

Coaxial Adapter 7/16 DIN Male to N Female

**Features / Benefits**



- **Low VSWR Performance**  
Excellent impedance matching minimizes reflections and ensures stable RF performance across the entire frequency range.
- **Low Insertion Loss**  
Minimal attenuation preserves signal quality and supports accurate, high-frequency signal transmission.
- **High PIM Performance**  
Outstanding intermodulation performance up to -163 dBc makes the adapters suitable for high-end RF and measurement applications.
- **Broad Frequency Range**  
Operates from DC to 6000 MHz, covering a wide range of test, measurement, and system integration needs.
- **Port Saver Functionality**  
Can be used as transition adapters or as port savers to protect sensitive measurement equipment from connector wear.
- **Robust Outdoor Design**  
IP86-rated housing enables reliable operation in demanding outdoor and industrial environments.

**Technical Features**

**STRUCTURE**

Product Type	Adapter
Interface A	7/16 DIN
Interface Gender A	Male
Center Contact Material A	silver plated brass
Outer Contact Material A	CuZnSn plated brass
Interface B	N
Center Contact Material B	silver plated spring bronze
Outer Contact Material B	CuZnSn plated brass
Body Material	nickel plated brass
Dielectric Material	PTFE
Gasket Material	silicone rubber

**ELECTRICAL SPECIFICATIONS**

Frequency Range	DC - 6000 MHz	
VSWR	1.06 (0-3000MHz)	1.10 (3000-6000MHz)
Insertion Loss	0.1 dB	
3rd Order IM Product @ 2x20 Watts	< -163 dBc	

**TESTING AND ENVIRONMENTAL**

Operation Temperature min.	-45°C (-49°F)
Sealing Class	IP68