



I-AT05-43-617/3800

Indoor Omnidirectional Antenna 617-3800MHz

Indoor Antenna, Omni



Features / Benefits

- **Wideband omnidirectional antenna**
Designed for broadband in-building DAS applications
- **Aesthetical visual appearance**
Blends easily into most building aesthetics with minimum visual impact
- **Superior electrical characteristics**
PIM optimized Antenna design and low return loss
- **Outstanding performance**
100 % PIM & VSWR tested
- **Easy installation, ceiling mounting**
Compact construction made of light weight materials for easy ceiling mounting
- **Indoor distribution of various communication services**

Technical Features

STRUCTURE

Product Type	Omnidirectional Antenna
Interface	4.3-10 female
Number of Ports	1
Mounting Hardware	Ceiling, via hole
Radome Material	ABS
Radome Color	White (RAL 9003)

MECHANICAL SPECIFICATIONS

Lenght (Less Connectors)	180mm (7.087in)
Width (Less Connectors)	150mm (5.905in)
Height (Less Connectors)	15mm (0.591in)
Weight	0.26kg (0.573lb)

ELECTRICAL SPECIFICATIONS

Polarization	Horizontal			
Impedance	50 Ω			
Total Input Power max.	50 W			
Intermodulation, 3rd Order	≤ -153 dBc			
Frequency Bands [MHz]	617-960	1427-1710	1710-2700	3300-3800
Gain [dBi]	3.5±1.0	4.0±1.0	4.5±1.0	5.0±1.0
Return Loss [dB] (VSWR)	10.9 (1.8)	10.9 (1.8)	10.9 (1.8)	10.9 (1.8)



I-AT05-43-617/3800

Indoor Omnidirectional Antenna 617-3800MHz

TESTING AND ENVIRONMENTAL

Ingress Protection (IP) Rating	Indoor
Maximum Humidity	< 95 %
Operation Temperature, Minimum	-40°C (-40°F)
Operation Temperature, Maximum	60°C (140°F)

