



SCF14-50J
1/4" CELLFLEX® Superflexible Foam-Dielectric Coaxial Cable



CELLFLEX® 1/4" superflexible cable

Features / Benefits

- Ultra Low Attenuation**
The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- Complete Shielding**
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- Low VSWR**
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- Outstanding Intermodulation Performance**
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical Features

STRUCTURE

Cable Type	SCF
Size	1/4"
Jacket Option	Outdoor
Inner Conductor Material	Copper-Clad Aluminium Wire
Dielectric Material	Foam Polyethylen
Outer Conductor Material	Corrugated Copper
Jacket Material	Black Polyethylen

MECHANICAL SPECIFICATION

Inner Conductor Diameter	1.9mm (0.075in)
Dielectric Diameter	4.3mm (0.169in)
Outer Conductor Diameter	6.5mm (0.256in)
Jacket Diameter	7.8mm (0.307in)
Cable Weight	0.07kg/m (0.047lb/ft)
Min. Bending Radius, Repeated Bends	25mm (0.984in)
Bending Moment	0.7Nm (0.517ft-lbf)
Tensile Strength	600N (134.885lb)
Max. Pulling Length per Hoisting Grip	60m (2,362.205in)
Recommended Clamp Spacing	0.2m (0.656ft)



SCF14-50J
1/4" CELLFLEX® Superflexible Foam-Dielectric Coaxial Cable

ELECTRICAL SPECIFICATION

Impedance	50 ±1 Ω
Max. Operating Frequency	20.4 GHz
Velocity	82 %
Capacitance	82pF/m (24.994pF/ft)
Peak Power Rating	5.5 kW
RF Peak Voltage	0.74 kV
Jacket Spark	5 kV
DC-Resistance Inner Conductor	10.4Ω/km (3.17Ω/kft)
DC-Resistance Outer Conductor	6.6Ω/km (2.012Ω/kft)
Return Loss (VSWR) Performance	Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies.

TESTING AND ENVIRONMENTAL

Fire Performance	Halogen Free
Compliance	RoHS 2011/65/EU China RoHS SJ/T 11364-2006 IEC 60754-1/-2 Halogen Acid Gases REACH (EC 1907/2006) IEC 60754-1/-2 Halogen Acid Gases
Phase Stabilized	Phase stabilized and phase matched cables are available upon request.
Installation Temperature, Minimum	-40°C (-40°F)
Installation Temperature, Maximum	60°C (140°F)
Storage Temperature, Minimum	-70°C (-94°F)
Storage Temperature, Maximum	85°C (185°F)
Operation Temperature, Minimum	-50°C (-58°F)
Operation Temperature, Maximum	85°C (185°F)

**SCF14-50J**

1/4" CELLFLEX® Superflexible Foam-Dielectric Coaxial Cable

ATTENUATION AND POWER RATING

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
75	5.02	1.53	1.32
100	5.82	1.77	1.14
150	7.17	2.19	0.92
200	8.33	2.54	0.79
450	12.73	3.88	0.52
700	16.1	4.91	0.41
800	17.29	5.27	0.38
870	18.09	5.51	0.37
900	18.42	5.62	0.36
960	19.07	5.81	0.35
1800	26.90	8.2	0.25
2000	28.51	8.69	0.23
2200	30.07	9.17	0.22
2400	31.57	9.62	0.21
2600	33.02	10.07	0.20
2700	33.73	10.28	0.20
3000	35.80	10.91	0.18
3500	39.09	11.92	0.17
4000	42.20	12.86	0.16
5000	48.03	14.64	0.14
6000	53.45	16.29	0.12
Note	Standard Conditions: For attenuation: VSWR 1.0, cable temperature 20°C (68°F). For average power: VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F). No solar loading.		

NOTES

SCFXX-50JTC: TC cables (temperature cycled) are cables that are aged in order to reduce hysteresis effects. Available upon request.