



**TPS10E-694/3800**

Unequal Divider/Tapper

RFS TPS\* Tapper product family has been designed to support a variety of wireless applications in the frequency band from 694 to 3800MHz. The units couple off a defined fraction of a RF signal from typically 3 to 30 dB with minimal reflections or loss. The broad frequency range is ideally suited for 3G / 4G / 5G multi-band distributed antenna systems or in combination with RADIAFLEX® radiating cables. Notably, these products feature a low level of network interferences due to their PIM optimized desing.



**Features / Benefits**

- **Split ratio 10:1 / 10dB**
- **N-female interfaces**
- **PIM optimized design (160dBc @2x43dBm)**
- **Low insertion loss**
- **High power handling**
- **Small size, Low weight**

**Technical Features**

**STRUCTURE**

Product Type	Unequal Divider/Tapper
Number of Input Ports	1
Number of Output Ports	2
Connector Type	N female

**MECHANICAL SPECIFICATIONS**

Height	49.7mm (1.96in)
Width	19.5mm (0.77in)
Length	84.3mm (3.32in)

**ELECTRICAL SPECIFICATIONS**

Impedance	50 $\Omega$
Frequency Range	694 - 3800 MHz
Return Loss ( max. VSWR)	17.7 dB (1.3)
Insertion Loss max.	0.5 dB
Intermodulation (IM3)	160dBc (2x43dBm)
Coupling Value	10.5 dB
Total Input Power	200 W

**TEMPERATURE SPECIFICATIONS**

Temperature Range	-25°C to 65°C (-13°F to 149°F)
-------------------	--------------------------------

**TESTING AND ENVIRONMENTAL**

Environmental Class	IP65
---------------------	------

External Document Links

Notes